



CommView for WiFi Technical Specifications

Supported WLAN Types

802.11a (5 GHz), 802.11b (2.4 GHz), 802.11g (2.4 GHz), 802.11n (2.4 and 5 GHz), 802.11ac (5 GHz), 802.11ax and 802.11be (2.4, 5, and 6 GHz).

Supported Adapters

The application supports many wireless adapters in the following form factors:

- USB
- mPCIe (integrated)

For the complete, up-to-date list of supported adapters, please visit [our website](#).

Spectrum Analysis (optional)

Live spectrum analysis can be performed by interfacing with WiPry, a tri-band USB spectrum analyzer by [Oscium](#).

System Requirements

- Intel Core 2 or higher
- 4 GB of RAM
- 250 MB of free disk space

Operating Systems

CommView for WiFi runs on 32-bit and 64-bit operating systems:

- Windows 10 and 11
- Windows Server 2016, 2019, and 2022

TCP/UDP Session Reconstruction Formats

- ASCII
- HEX
- HTML
- UTF-8
- EBCDIC

Report Formats

- HTML
- CSV
- Text files
- Bitmap files

WPA/WEP Support

On-the-fly decryption of 64, 128, 152, and 256-bit WEP-encrypted packets with a user-defined WEP key. On-the-fly decryption of WPA/WPA2-encrypted packets in PSK mode with a user-defined WPA passphrase. TKIP and AES modes supported.

Supported Capture File Formats

- CommView native format (NCFX)
- Network Instruments Observer®
- Network General Sniffer® for DOS
- Network General Sniffer® for Windows
- Microsoft® NetMon
- WildPackets EtherPeek™
- WildPackets AiroPeek™
- Wireshark/Tcpdump (pcap)
- Wireshark/ Pcapng
- Plain ASCII

Copyright © 1998-2024 TamoSoft. All Rights Reserved. No part of this document can be reproduced, duplicated or modified in any form, including electronic means, without the express written permission of TamoSoft. CommView is a registered trademark of TamoSoft. All other product names and trademarks are the property of their respective holders.